

Giada

design **Enrico Davide Bona** e **Elisa Nobile**

La serie di applique Giada combina le nuove sorgenti LED COB ad alta potenza, con un sistema di dissipazione termica passiva. Due i modelli progettati: Giada è il perfetto connubio tra miniaturizzazione e alta efficienza; Giada 200 ha dimensioni più grandi e integra LED di potenza elevata, per prestazioni illuminotecniche ottimali. La loro speciale forma si adatta alla parete in maniera discreta e accattivante, ottenendo una diffusione luminosa piacevole e funzionale. I fori nella parte superiore e inferiore dell'apparecchio enfatizzano il colore della parete retrostante e creano giochi di luce di grande effetto.

The Giada range of wall luminaires have been developed to use the new powerful COB LED sources in an innovative design, with a passive heat dissipation. The fitting is available in two models: Giada is the ideal combination of miniaturization and high efficiency; while Giada 200 has a larger size and it is equipped with high power LEDs, for optimal lighting performance. Their special shape fits on the wall with a sober and appealing look, providing a pleasant and functional light diffusion. The holes in the upper and lower parts of the fitting have been designed to emphasize the colour of the wall behind, and to create scenic light effects.

Materiali:

- Corpo e attacco a parete
in pressofusione di alluminio
verniciato poliestere

Materials:

- Body and wall bracket
in die-cast aluminium,
polyester painted





Giada prevede un LED per luce monodirezionale. Giada 200 è disponibile nelle versioni bidirezionale a doppia accensione oppure monodirezionale. Il corpo, inclinabile di $\pm 12^\circ$ nel piano verticale, permette di orientare il fascio luminoso emesso.



Giada is available in a one-LED version for monodirectional light. Giada 200 is available in a bi-directional double switch or in a single light version. The body can tilt by $\pm 12^\circ$, with the possibility of pointing the luminous flux accordingly.

GIADA 200



Codice Code	LED Lumen	Product Lumen	Watt	Colour T (K)	CRI	Fascio Beam
----------------	--------------	------------------	------	-----------------	-----	----------------

Bidirezionale a doppia accensione (su richiesta) / Bi-directional double switch (on demand)

3741-01	6800+1800	6120+1620	51+12	3000	85	115°/115°
---------	-----------	-----------	-------	------	----	-----------

Monodirezionale / Single light

3743-01	6800	6120	51	3000	85	115°
---------	------	------	----	------	----	------



220/240V – 50/60Hz

CE


850°

IP20


luci da parete / wall lights



3,4 kg



115°/115°



115°