

Proiettori per esterni

Exterior projectors

L’accento è sull’esterno

Danno il loro meglio negli spazi esterni dove è richiesta una luce d’accento. Accessoriabili con snoot asimmetrico per direzionare il fascio luminoso e ridurre l’abbagliamento, si distinguono per la purezza della forma cilindrica.

The focus is on the exterior

These projectors are well suited for accent lighting in exterior spaces. Accessories include an asymmetric snoot to shield the light beam and reduce glare. The purity of their cylindrical shape makes them original and unique products.

L’eleganza di essere micro

The elegance of being micro

Un’attenta ricerca in sviluppo e progettazione è a fondamento della creazione di questi nuovi proiettori. Una gamma che fa del minimalismo un elemento distintivo con la volontà di rendere i prodotti quasi impercettibili. Lo scopo è quello di limitare al massimo l’aspetto invasivo dell’apparecchio e focalizzarsi su ciò che è importante, ovvero gli elementi da valorizzare.

Extensive research in development and design is the foundation to produce these new and highlevel projectors. This range performs minimalism as its key feature, with almost imperceptible products, minimizing the invasive appearance of the fitting, focusing on the details to be enhanced.

Possono essere accessoriati con snoot asimmetrico per direzionare il fascio luminoso e ridurre l’abbagliamento. Numerose le applicazioni: a parete, a soffitto, a pavimento oppure nel terreno con l’apposito picchetto.

These projectors can be equipped with an asymmetrical snoot to shield off the light beam and to reduce glare. They are suitable for many applications: wall mounted, ceiling mounted, floor mounted on a base or ground spike.



Caratteristiche Tecniche

Corpo in pressofusione di alluminio, verniciato poliestere, con speciale pretrattamento antiossidante.
Riflettori in termoplastico metallizzato a specchio.
Lenti intercambiabili in PMMA (microperfetto).
Vetro di protezione temprato e molato (3mm).
Guarnizioni siliconiche.

Technical Specifications

Body in die-cast aluminum polyester painted, with a special antioxidant pre-treatment.
Reflectors in mirror metallized thermoplastic material.
PMMA replaceable lenses (microperfetto).
Grinded, tempered safety glass (3 mm).
Silicone gaskets.

Apparecchi dal design coerente che ben si adattano a contesti architettonici e spazi diversi: dalle applicazioni a plafone o a terra in esterno, su staffa, con picchetto o paletto, a quelle per ambienti interni dove è richiesto un alto rendimento illuminotecnico, ma anche un ottimo livello di protezione contro l'accesso di liquidi, come bagni e spa.

Luminaires with a consistent design that are well suited to different architectural settings and locations: from outdoor ceiling or ground applications, with spike, bracket or pole, to ceiling mounted indoor installations, such as bathrooms and spas, where a high lighting performance, but also an excellent level of protection against the passage of liquids are needed.






PERFETTO IP66



Codice Code	Colore Colour	LED Lumen	Product Lumen	Watt	Colour T (K)	CRI	Fascio Beam
10350030	Nero / Black	2400	1778	18	3000	85	26°
1035A0030	Nero / Black	2450	1816	18	4000	85	26°
10370030	Nero / Black	3500	2594	30	3000	85	29°
1037A0030	Nero / Black	3590	2660	30	4000	85	29°




1,4 kg

18W: Regolabile sulla fase / Dimmable on the mains

220/240V - 50/60Hz

IP66 IK10

Accessori ottici intercambiabili
Replaceable optical accessories

28-9001-51
Ottica professionale S
Professional optic device S

18W







28-9002-51
Ottica professionale M
Professional optic device M

18W



28-9003-51
Ottica professionale W
Professional optic device W

18W







28-4163-30
Frangiluce alveolare
(per 18W)
Honeycomb
(for 18W)



28-04191-47
Vetro zigrinato
(per 18W)
Prismatic spread lens
(for 18W)

28-3901-51
Ottica professionale S
Professional optic device S

30W







28-3902-51
Ottica professionale M
Professional optic device M

30W



28-3903-51
Ottica professionale W
Professional optic device W

30W






28-3903-31
Ottica professionale XW
Professional optic device XW

30W






28-4208-30
Frangiluce alveolare
(per 30W)
Honeycomb
(for 30W)



28-04190-47
Vetro zigrinato
(per 30W)
Prismatic spread lens
(for 30W)




28-4130-30
Cilindro asimmetrico
Asymmetric snoot

Accessori su richiesta
Accessories on demand



28-2377-30
Picchetto in termoplastico
nero / Black thermoplastic
spike



84108
Connettore stagno
Rated cable connector

